

HITANO ENTERPRISE CORPORATION

Application Notes.

Subject : Storage of Chip Resistor

We recommend the following storage conditions :

To prevent damage to terminal soldering performance, the following storage and handling conditions are recommended :

- (1) Store the product at an ambient temperature of 5 ~ 40°C and a relative humidity of 20% ~ 70%.
- (2) It is recommended that the product be used within one year of shipment.
To extend the shelf life of 12 ~ 24 months is required, the solderability must be checked before use.

Precautions :

- a. Do not store resistors in environments containing sulfuric acid, hydrogen sulfide, sulfur dioxide, chlorine, ammonia, etc.
Corrosive gases react with the resistors terminals, reducing its solderability, and may cause silver migration, thereby reducing reliability.
- b. Only open the packaging when the resistors is needed.
If the packaging has been opened, reseal it as soon as possible.
Products packaged with tape should be kept away from direct sunlight to prevent the tape or adhesive from aging.
- c. Do not store resistors in direct sunlight or in environments with condensation.
Rapid changes in humidity leading to condensation, or direct sunlight causing photochemical changes in the terminal electrodes, may reduce solderability.
- d. Please store the product on a shelf to prevent it from getting damp.

For and on behalf of
HITANO ENTERPRISE CORP.


Authorized Signature

Approved by : _____

Prepared by : Randy Yu