

●14D series

Model Number		Maximum Allowable Voltage		Varistor Voltage V _{1.0mA} (V)	Clamping Voltage (MAX.)		Maximum Peak current (8/20μs)		Maximum Energy (10/1000μs)		Rated Power (W)	Typical Capacitance (Reference) @1KHz (pf)	UL	D'E				
					VC (V)	IP (A)	Standard (A)	High Surge	Standard	High Surge								
Standard	High Surge	AC (V)	DC (V)															
14D180L	J	11	14	18(15-21)	36	10	1000	2000	4.0	7.0	0.1	11100	*					
14D220K	J	14	18	22(20 -24)	43				5.0	8.0		9100	*					
14D270K	J	17	22	27(24 -30)	53				6.0	10		7400	*	*				
14D330K	J	20	26	33(30 -36)	65				7.5	12		6100	*	*				
14D390K	J	25	31	39(35 - 43)	77				8.6	13		5100	*	*				
14D470K	J	30	38	47(42 - 52)	93				10	17		4300	*	*				
14D560K	J	35	45	56(50 - 62)	110				11	20		3600	*	*				
14D680K	J	40	56	68(61 - 75)	135				14	24		2900	*	*				
14D820K	J	50	65	82(74 - 90)	135				50	4500		6000	22	27	0.6	2400	*	*
14D101K	J	60	85	100(90 - 110)	165								28	33		2000	*	*
14D121K	J	75	100	120(108 - 132)	200	32	40	1700			*		*					
14D151K	J	95	125	150(135 - 165)	250	40	53	1300			*		*					
14D181K	J	115	150	180(162 - 198)	300	50	60	1100			*		*					
14D201K	J	130	170	200(185 - 225)	340	57	70	1000			*		*					
14D221K	J	140	180	220(198 - 242)	360	60	78	900			*		*					
14D241K	J	150	200	240(216 - 264)	395	63	84	830			*		*					
14D271K	J	175	225	270(243 - 297)	455	70	99	740			*		*					
14D301K	J	190	250	300(270 - 330)	500	77	108	670			*		*					
14D331K	J	210	275	330(297 - 363)	550	85	115	610			*		*					
14D361K	J	230	300	360(324 - 396)	595	93	130	560			*		*					
14D391K	J	250	320	390(351 - 429)	650	100	140	510			*		*					
14D431K	J	275	350	430(387 - 473)	710	115	155	460			*		*					
14D471K	J	300	385	470(423 - 517)	775	125	175	430			*		*					
14D511K	J	320	415	510(459 - 561)	845	125	180	390			*		*					
14D561K	J	350	460	560(504 - 616)	925	125	185	360			*		*					
14D621K	J	385	505	620(558 - 682)	1025	125	190	320			*		*					
14D681K	J	420	560	680(612 - 748)	1120	130	200	290			*		*					
14D751K	J	460	615	750(675 - 825)	1240	143	210	270			*		*					
14D781K	J	485	640	780(702 - 858)	1290	148	220	260			*							
14D821K	J	510	670	820(738 - 902)	1355	157	235	240			*							
14D911K	J	550	745	910(819 - 1001)	1500	176	255	220			*							
14D102K	J	625	825	1000(900 - 1100)	1650	190	280	200			*							
14D112K	J	680	895	1100(990 - 1210)	1815	213	310	180			*							
14D122K	J	720	980	1200(1080-1320)	1980	232	324	160			*							
14D142K	J	825	1135	1400(1260-1540)	2310	238	327	150			*							
14D152K	J	860	1220	1500(1350-1650)	2440	240	320	150			*							
14D162K	J	920	1300	1600(1440-1760)	2640	243	331	140	*									
14D182K	J	1100	1465	1800(1620-1980)	2970	5000	250	335	130	*								

OPERATING TEMPERATURE RANGE: - 40°C ~ +105°C

STORAGE TEMPERATURE RANGE: - 40°C ~ +125°C

● **14D series**

