

Data Sheet

Customer : _____

Product : Conductive Polymer Hybrid Aluminum Electrolytic Capacitors
SMD Type, High Temperature, 145°C 2,000Hours – AHMY Series
AEC-Q200 Version Available

Size : 8x10mm ~ 10x10.5mm

Issued Date : 01-Sep.-2025

Edition : Ver.1

Record of change

Date	Ver.	Description	Page

HITANO ENTERPRISE CORP.

7F-7, No. 3, Wu Chuan 1st Road, New Taipei Industrial Park,
New Taipei City, TAIWAN, R.O.C.
Tel: +886 2 2299 1331 (Rep.)
Fax: +886 2 2298 2466, 2298 2969

Prepared by	Checked by	Approved by	Accepted by (customer)
01-Sep.-2025	01-Sep.-2025	01-Sep.-2025	
Randy Yu	Michelle Lin	Arthur Su	

CONDUCTIVE POLYMER HYBRID ALUMINUM ELECTROLYTIC CAPACITORS


SMD Type, 145°C High Temperature

- High reliability and high voltage realized by hybrid electrolyte
- Endurance: 2,000 hours at 145°C
- Rated Voltage : 25V ~ 63V
- Rated capacitance : 33 ~ 330 μ F
- For high temperature & reliability applications.
- AEC-Q200 Compliant, for automotive equipment.

SPECIFICATIONS

Item	Performance Characteristics															
Operating Temperature range	-55 + 145°C															
Rated Voltage Range	25V ~ 63V															
Capacitance Tolerance	± 20% (at 120 Hz/ 20°C)															
Leakage Current	I ≤ 0.01 CV or less (2 minutes , 20°C) Not greater than the formula above after 2 minutes voltage applied. I : Leakage current (μA) C : Capacitance (μF) V : Voltage(VDC)															
Dissipation Factor (tan δ)	Rated voltage(V)	25	35	50	63	(20°C · 120 Hz)										
	tan δ (Max.)	0.14	0.12	0.10	0.08											
Temperature Characteristics (Impedance ratio at 100 KHz)	Z (-25°C)/ Z (+20°C) < 2.0 Z (-55°C)/ Z (+20°C) < 2.5															
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 2,000 hours at 145°C. <table><tr><td>Capacitance change</td><td>≤ ± 30% of the initial value</td></tr><tr><td>D. F. (Tan δ)</td><td>≤ 200% of initial specified value</td></tr><tr><td>ESR</td><td>≤ 200% of initial specified value</td></tr><tr><td>Leakage current</td><td>Initial specified value or less</td></tr></table>						Capacitance change	≤ ± 30% of the initial value	D. F. (Tan δ)	≤ 200% of initial specified value	ESR	≤ 200% of initial specified value	Leakage current	Initial specified value or less		
Capacitance change	≤ ± 30% of the initial value															
D. F. (Tan δ)	≤ 200% of initial specified value															
ESR	≤ 200% of initial specified value															
Leakage current	Initial specified value or less															
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 145°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to item 4.1 of JIS C 5101-4. <table><tr><td>Capacitance change</td><td>≤ ± 30% of the initial value</td></tr><tr><td>D. F. (Tan δ)</td><td>≤ 200% of initial specified value</td></tr><tr><td>ESR</td><td>≤ 200% of initial specified value</td></tr><tr><td>Leakage current</td><td>Initial specified value or less</td></tr></table>						Capacitance change	≤ ± 30% of the initial value	D. F. (Tan δ)	≤ 200% of initial specified value	ESR	≤ 200% of initial specified value	Leakage current	Initial specified value or less		
Capacitance change	≤ ± 30% of the initial value															
D. F. (Tan δ)	≤ 200% of initial specified value															
ESR	≤ 200% of initial specified value															
Leakage current	Initial specified value or less															
Bias Humidity Test	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjecting them to the DC rated voltage at 85°C, 85% RH for 2,000 hours. <table><tr><td>Capacitance change</td><td>≤ ± 30% of the initial value</td></tr><tr><td>D. F. (Tan δ)</td><td>≤ 200% of initial specified value</td></tr><tr><td>ESR</td><td>≤ 200% of initial specified value</td></tr><tr><td>Leakage current</td><td>Initial specified value or less</td></tr><tr><td>Appearance</td><td>No significant damage</td></tr></table>						Capacitance change	≤ ± 30% of the initial value	D. F. (Tan δ)	≤ 200% of initial specified value	ESR	≤ 200% of initial specified value	Leakage current	Initial specified value or less	Appearance	No significant damage
Capacitance change	≤ ± 30% of the initial value															
D. F. (Tan δ)	≤ 200% of initial specified value															
ESR	≤ 200% of initial specified value															
Leakage current	Initial specified value or less															
Appearance	No significant damage															
Resistance to Soldering heat	The following specifications shall be satisfied when the capacitors are restored to 20°C after the soldering. <table><tr><td>Capacitance change</td><td>≤ ± 10% of the initial value</td></tr><tr><td>D. F. (Tan δ)</td><td>≤ the initial specified value</td></tr><tr><td>Leakage current</td><td>≤ the initial specified value</td></tr></table>						Capacitance change	≤ ± 10% of the initial value	D. F. (Tan δ)	≤ the initial specified value	Leakage current	≤ the initial specified value				
Capacitance change	≤ ± 10% of the initial value															
D. F. (Tan δ)	≤ the initial specified value															
Leakage current	≤ the initial specified value															

Dimension



ØD	L	A	B	C	H	E
8	10.0	8.3	8.3	9	0.7~1.1	3.1
10	10.5	10.3	10.3	11	0.7~1.1	4.5

CONDUCTIVE POLYMER HYBRID ALUMINUM ELECTROLYTIC CAPACITORS

■ Part Numbering (example: 100 μ F 50V 10x10.5mm)

A H M Y	1 0 1	M	1 H	C	R	E	1 0 5	S
SERIES	CAPACITANCE	TOL.	W.V.	TYPE	LEAD	DIA.	LENGTH	PRINTING COLOR

■ Standard Products Table

Rated voltage (V.DC)	Rated Capacitance (μF)	Case Size D x L (mm)	tan δ	ESR (mΩ max. 20°C/100 KHz)	Rated ripple current (mA rms/100KHz)	
					≤ 135°C	≤ 145°C
25 (1E)	220	8 x 10	0.14	27	1,600	700
	270	10 x 10.5	0.14	20	2,000	900
	330	10 x 10.5	0.14	20	2,000	900
35 (1V)	150	8 x 10	0.12	27	1,600	700
	220	10 x 10.5	0.12	20	2,000	900
	270	10 x 10.5	0.12	20	2,000	900
50 (1H)	68	8 x 10	0.10	30	1,250	600
	82	10 x 10.5	0.10	28	1,600	800
	100	10 x 10.5	0.10	28	1,600	800
63 (1J)	33	8 x 10	0.08	40	1,100	600
	56	10 x 10.5	0.08	30	1,400	800
	68	10 x 10.5	0.08	30	1,400	800
	82	10 x 10.5	0.08	30	1,400	800

■ **Frequency coefficient of allowable ripple current**

Frequency	120 Hz < f < 1 KHz	1 KHz < f < 10 KHz	10 KHz < f < 100 KHz	100 KHz < f < 300 KHz
Coefficient	0.20	0.40	0.70	1.00