

Data Sheet

Customer: _____

Product: Aluminum Electrolytic Capacitors – EHR Series _____

Size : 5x11mm ~ 22x41mm _____

Issued Date: 28-Mar.-2022 _____

Edition: Ver. 3 _____

Record of change

Date	Ver.	Description	Page
25-Jun.-2016	1		
05-Jan.-2021	2	revised sizes 3.3uF 450V	3
28-Mar.-2022	3	Add 330uF 250V	3
28-Mar.-2025	4	Add 1000uF 16V 10x13	2

HITANO ENTERPRISE CORP.

7F-7, No. 3, Wu Chuan 1st Road, New Taipei Industrial Park,

New Taipei City, TAIWAN, R.O.C.

Tel: +886 2 2299 1331 (Rep.)


Fax: +886 2 2298 2466, 2298 2969

Prepared by	Checked by	Approved by	Accepted by (customer)
28-Mar.-2025	28-Mar.-2025	28-Mar.-2025	
<i>Randy Yu</i>	<i>Michelle Lin</i>	<i>Arthur Su</i>	

- High Temperature Radial Type, 105°C, 2000 hours assured Load Life.
- Applications: Communications equipment, switching regulators, and industrial applications.

Characteristics

Voltage Range	6.3 to 100 VDC				160 to 450 VDC			
Capacitance Range	0.47 to 10000uF				0.47 to 220uF			
Temperature Range	-40 to +105°C				-25 to +105°C			
Capacitance Tolerance	±20% at 120Hz, 20°C (10% Tol. is available upon request)							
Leakage Current	I ≤ 0.01CV or 3uA, whichever is greater 2 minutes after Rated Voltage applied				I ≤ 0.03CV + 20uA, whichever is greater 2 minutes after Rated Voltage applied			
Dissipation Factor	Rated Voltage (V)	6.3	10	16	25	35	50	63
	Dissipation Factor(tanδ)max	0.22	0.20	0.16	0.14	0.12	0.10	0.09
	Rated Voltage (V)	100	160	200	250	350	400	450
	Dissipation Factor(tanδ)max	0.08	0.12	0.14	0.17	0.20	0.25	0.25
For capacitance > 1000uF, add 0.02 for every 1000uF, (at 20°C, 120Hz)								
Stability at Low Temperature (Impedance ratio at 120Hz) (For Cap. > 1000uF, add 0.5 per 1000uF(-25°C/+20°C) add 1.0 per 1000uF(-40°C/+20°C)	Rated Voltage (V)	6.3	10	16	25	35	50	63
	Z-25°C/Z 20°C	4	3	2	2	2	2	2
	Z-40°C/Z 20°C	8	6	4	3	3	3	3
	Rated Voltage (V)	160	200	250	350	400	450	
	Z-25°C/Z 20°C	2	2	3	5	6	6	
Load Life	After the rated voltage has been applied for 2000 hours at 105°C	Capacitance change	Within ±20% of initial value					
		D.F. tanδ	200% or less of initial specified value					
		Leakage current	Less than initial specified value					
Shelf Life	After storage for 1000 hours at 105°C with no voltage applied, the capacitor shall meet the specified limit in load life. Pre-treatment for measurement shall be conducted after application of DC working voltage for 30 minutes.							



Drawing

Dφ	5	6.3	8	10	13	16	18	22
p	2.0	2.5	3.5	5.0	5.0	7.5	7.5	10
dφ	0.5	0.5	0.5	0.6	0.6	0.8	0.8	0.8

Ripple Current Coefficients

Frequency (Hz)	50(60)	120	400	1K	10K	100K
Cap.(uF) / Hz	Multiplier					
Cap. ≤ 10	0.8	1	1.30	1.45	1.65	1.70
10 < Cap. ≤ 100	0.8	1	1.23	1.36	1.48	1.53
100 < Cap. ≤ 1000	0.8	1	1.16	1.25	1.35	1.38
1000 < Cap.	0.8	1	1.11	1.17	1.25	1.28

Case Size & Maximum Ripple Current (mA rms 105°C 120Hz)

Cap. wv	100V(2A)		160V(2C)		200V(2D)		250V(2E)		350V(2V)		400V(2G)		450V(2W)	
	uF	Size	R.C.	Size	R.C.	Size	R.C.	Size	R.C.	Size	R.C.	Size	R.C.	Size
0.47	5x11	10	5x11	12	5x11	12	5x11	12	6.3x11	13	6.3x11	14	6.3x11	14
1	5x11	15	5x11 6.3x11	17 19	6.3x11	17	6.3x11	17	6.3x11	20	6.3x11 8x12	17 20	8x12	20
2.2	5x11	23	6.3x11	25	6.3x11	25	6.3x11 8x12	20 25	8x12	31	8x12 10x13	35 40	8x12 10x13	30 35
3.3	5x11	32	6.3x11	32	6.3x11 8x12	33 35	8x12	42	8x12 10x13	46 50	8x12 10x13	36 41	8x12 10x13 10x16	32 38 42
4.7	5x11	37	6.3x11 8x12	38 42	6.3x11 8x12	42 50	8x12 10x13	46 50	8x12 10x13	47 52	10x13 10x16	55 65	10x16 10x21	50 60
6.8	6.3x11	47	8x12	56	8x12 10x13	60 63	8x12 10x13	60 70	10x13	79	10x16	84	10x16 10x21	65 72
10	6.3x11	56	8x12 10x13	63 75	8x12 10x13	78 85	10x16	64	10x16 10x21	87 79	10x21 13x21 10x12.5	111 125 104	13x21 13x26	80 87
22	6.3x11 8x12	75 96	10x13 10x16	95 105	10x16 10x21	105 130	10x21 13x21	110 140	13x21 13x26	130 160	13x26 16x26	160 190	16x26 16x31.5	165 200
33	8x12 10x13	140 155	10x16 10x21	155 170	10x21 13x21	180 190	13x21	190	13x26 16x26	200 220	13x26 16x26	220 235	16x31.5 16x36	210 230
47	10x13 10x16	160 170	10x21 13x21	180 210	13x21 13x26	165 220	13x26 16x26	220 240	16x26 16x31.5	245 260	16x31.5 16x36	250 275	16x36 18x31.5	260 290
68	10x16	240	13x21 13x26	260 280	13x21 13x26	270 300	13x26 16x26	310 355	16x31.5	370	16x31.5 16x36	450 480	18x31.5 18x36	460 470
100	10x21 13x21	245 280	13x26 16x26	310 330	13x26 16x26	320 345	16x26 16x31.5	365 395	18x31.5 18x36	375 390	18x31.5 18x36	530 550	18x36 18x41	525 560
150	13x21 13x26	340 360	16x26	470	16x26 16x31.5	440 480	16x36 18x31.5	460 460	18x41	420	18x36 18x41	610 650	22x41	650
220	13x26 16x26	450 520	16x31.5 16x36	560 580	18x36 18x31.5	670 690	18x36 22x41	650 700						
330	13x21 13x26 16x26	874 660 690	18x31.5 18x36	660 700	18x31.5 18x36	750 810	18X45 25X30	720 800						
470	16x26 16x31.5	820 860	18x36 18x41	810 860	18x41 22x41	840 925								
680	16x36 18x31.5	920 950												
1000	18x41	1200												

Part Numbering System

EHR	101	M	25	A	-	T1
SERIES	CAPACITANCE	TOL.	W.V.	PACKAGE	SIZE	LEAD SPACE
	IN 3DIGITS	M= ± 20%	0J= 6.3V	B= Bulk	Omit if only	Omit if Bulk
	010= 1.0uF		16= 16V	C5= Cut 5mm	one size	T1= L/S 2.5mm Taped
	4R7= 4.7 uF		63= 63V	AC5= Smaller Size cut 5mm	A= Smaller Size	TA= Lead forming space 5mm Taped
	101= 100uF		2A=100V			
	102= 1000uF		(Refer to voltage code in table)	A= Ammo Pack		T35= L/S 3.5mm Taped
	103= 10000uF			R= Tape&Reel		T2=L/S 5mm Taped
				F5= Lead formed & cut 5mm		T3= L/S 7.5mm Taped